

# we are proven

Our capacitors keep the Royal Navy moving

AC CAPACITORS



[www.api-capacitors.com](http://www.api-capacitors.com)

 **apicapacitors**

## AC CAPACITORS

API Capacitors design and manufacture AC capacitors that are not limited to a catalogue range. Current, voltage, size, mass and terminations are matched to the customer's requirement and application, a few of which are listed below.

Long life and high reliability is achieved using ultra low defect density, high isotactic, metallised polypropylene dielectric film incorporating an extended working temperature range and controlled self-healing capability. Elements are wound on the latest precision edge controlled automatic winding machines. High conductivity copper is used for low resistance internal connections. Capacitors are finished in powder coated corrosion free metal or insulated cases and filled with an environmentally safe oil or dry leak free resin.

### Typical Applications\*

Used in Transportation, Marine, Automotive, Aerospace, Military, Medical, Renewable Energy, Power Distribution sectors and other industrial applications.

- Static Drives (Elevators, Escalators, Conveyors, Cable Cars)
- Non-static Drives (Propulsion, Traction)
- Power Electronics (Welding, Furnaces, Induction Heating)
- Power Transmission (Conditioning, Detuned, FACTS, STATCOM, SVC, PFC)
- Passenger/Freight Rail (Line Filters, Signalling, Auxiliary Circuits)
- Filters (Smoothing, Suppression, Harmonic)
- Converters (Inverters, Rectifiers, Choppers, Cycloconverters)

### Features

- Long Life and High Reliability
- Controlled Self-Healing Technology
- Oil Filled or Dry Resin Filled
- Metal or Insulated Cases
- UV Resistance, Halogen Free, Low Smoke and Flame Retardant Materials

### Custom Design Capacitors

Designed to meet detailed or brief specifications. Our technical sales representatives can work closely with your design team at concept stage or at the later stages of a project when a time critical design is needed. Alternatively like for-like replacements for older retro-fit designs can be offered.

### Typical Characteristics\*

<b>Rated Capacitance (C):</b>	0.05 to 5500 $\mu$ F
<b>Peak Repetitive Voltage (<math>U_N</math>):</b>	100 to 25,000 V
<b>Continuous RMS Current (<math>I_{max}</math>):</b>	10 to 1,000 $A_{rms}$
<b>Frequency (<math>f_p</math>):</b>	50/60 to 100,000 Hz
<b>Ambient Temperature (<math>\theta_{amb}</math>):</b>	-40 to +85 °C
<b>Case Materials:</b>	Steel, Stainless Steel, Aluminium and Various Insulated Materials
<b>Termination:</b>	Threaded M5-M16 Copper/Brass, Ceramic/Polymer Insulators, Busbar, Cable and Laminated connections
<b>Related Standards:</b>	BS EN 61071, BS EN 61881



\* Applications and characteristics are for guidance only. Please contact us to discuss our full design capability.